

Window Blinds



Model: Visage Blinds

Size: Custom

Support Material: Aluminum

Fabric: Custom Finish

Installation: Optional

Brand: NERVAL

Warranty: Limited 1 year

Nerval Visage Blinds can be operated with manual cords or with motorized control. Nerval's Visage Blinds pair sheer with fabric vanes for superb light control, striking a perfect balance between form and function. Both the manual and the motorized options provide smooth, easy functionality.

Features:


- · Elegant, subdued look and quiet movement
- Outer sheer layers provide privacy, even when the vanes are open
- Perfectly symmetrical alignment of vanes
- Brackets offer adjustment for installations where leveling is needed
- Simple installation for both inside mount and outside mount
- Blind components are designed for quiet operation
- Hardwired & Battery operated motorization available
- Fabric wrapped fascia available to match the blind's vanes

Disclaimer: Nerval makes every effort to provide accurate specification data. However, specification may change without notice. Please visit nerval website to see NERVAL'S TERMS AND CONDITONS.





Window Blinds

Hardware Details:




Installed Profile: 2 inch Blind (Fascia end caps and some other details omitted for clarity.)





Installed Profile: 3 inch Blind (Fascia end caps and some other details omitted for clarity.)



NOTE: Due to the fabric expansion in the fully-lowered position, a pocket flap cannot be used with Horizointal Sheer Blinds.

Disclaimer: Nerval makes every effort to provide accurate specification data. However, specification may change without notice. Please visit nerval website to see NERVAL'S TERMS AND CONDITONS.



Window Blinds


Mounting Options

Depending on the window dimensions, the shade can be mounted inside the window frame or outside the window frame.


INSIDE MOUNT

To use inside mount, the window depth must be at least: 2 1/4 in (57 mm) for both 2 in and 3 in vane


For fully recessed installation, the window depth must be at least: 3 3/4 in (95 mm) for 2 in vane, 4 1/2 in (114 mm) for 3 in vane



OUTSIDE MOUNT ON TRIM:



OUTSIDE MOUNT ABOVE TRIM:



Disclaimer: Nerval makes every effort to provide accurate specification data. However, specification may change without notice. Please visit nerval website to see NERVAL'S TERMS AND CONDITONS.